

ABS Caliper Cover Installation Guide

Preparation

It is important to clean and prepare your work area before you begin the job. Because you will be working on the brake calipers you will need to remove the wheels from the vehicle which will require you to jack the vehicle up which must be done on a flat and level surface. DO NOT ATTEMPT INSTALLATION ON A GRADE OR INCLINE.

Recommended Tools & Supplies

You will need the following tools and supplies to complete your installation of ABS Caliper Covers quickly and without difficulty:

- Sand-paper or a wire brush
- High-heat silicone glue
- A marker or grease pencil
- Razor blade or, Dremel tool bench grinder

Installation Instructions

Step 1: Remove Wheel and Rims

Step 2: Clean Caliper and Brakes

Step 3: Test for fitment

After having removed the wheel and rim position the ABS caliper cover in the desired location. Using masking tape, affix the cover to the caliper and re-attach the rim. If it spins freely you may continue to Step 5. If it does not you may need to modify the cover as detailed in Step 4.

Step 4: Trim ABS Caliper Cover for Fitment (Optional Step)

If the caliper cover is too large, makes contact with any of the moving parts of the caliper, brake or rim you will need to trim it to fit.

In order to determine what needs to be trimmed proceed to mark the caliper with a marker or grease pencil.

Using a bench-grinder or hand-grinder you can easily trim of the excess plastic. You may also use a razor blade to score it and then break off the pieces of the cover.

Test for fitment after modifying and repeat until the cover fits as desired.

ABS Caliper Cover Installation Guide

Step 5: Abrade Surface of Caliper and Cover

Because we will be using silicone-based adhesives to apply the covers we need to ensure that the installation surfaces are well prepared. Using a wire wheel or coarse grain sandpaper abrade the areas where the cover and the caliper meet.

Step 6: Apply High Heat Silicone Glue to Caliper and Cover

Be sure that you DO NOT apply the caliper cover to the moving part of the caliper as this will cause it to pop off during braking.

Step 7: Tape Caliper Cover in Place and Allow to Cure for 24 Hours

Apply the glue liberally to the installation points that have been pre-sanded. Use masking tape to hold in position for at least 24 hours (curing times vary by product so be sure to follow directions).